

CONTROL



PL4+



PL4+D

	Max. inputs	Max. inputs = Onboard + modules		Max outputs	Max output = Onboard + modules	
		Onboard 4-20mA analogue	Max. inputs via modules, expansions and/or RS485		Onboard Relay	Max outputs via modules with Open Collector and/or relay
PL4+	8	4	4	21	5	16
PL4+D	12	4	8	21	5	16
MULTISCAN 8+	16	8	8	38	6	32
MULTISCAN 8+16	24	8	16	54	6	48
MULTISCAN ++ S1	40	8	32	72	8	64
MULTISCAN ++ S1	72	8	64	136	8	128
MULTISCAN ++ S1	136	8	128	264	8	256
MULTISCAN ++ S1	264	8	256	520	8	512
MULTISCAN++ S2	40	8	32	72	8	64
MULTISCAN++ S2	72	8	64	136	8	128
MULTISCAN++ S2	136	8	128	264	8	256
MULTISCAN++ S2	264	8	256	520	8	512
MULTISCAN++PK-8D	12	4	8	21	5	16
MULTISCAN++PK	40	8	32	72	8	64
MULTISCAN++PK	72	8	64	136	8	128
MULTISCAN++PK	136	8	128	264	8	256
MULTISCAN++PK	264	8	256	520	8	512
MULTISCAN++MED	72	8	64	136	8	128